

aerl

CoolMax SRX-R Charge Module

2U Solar MPPT



The **CoolMax SRX-R** features over thirty years of AERL's MPPT and Battery Charging experience, offering a superior tracking algorithm, an ultra-low loss, high efficiency thermal design, backed by our Australian factory warranty and local support.

With record-breaking conversion efficiencies, intelligent thermal management, and state of the art MPPT tracking, the SRX is a key component of any high-quality DC-Coupled power system.

Product Highlights

- 2U Rack Format for Ease of Install and Servicing
- Scalable for Large Storage Applications
- Remote Module Control & Monitoring
- Utility Grade - for Long Term Reliability
- PV Array Oversizing Support (+50%)
- Reverse Polarity and Current Protection
- Built-In Overload and Thermal Protection
- On-Board Ground Fault Detection



Australian Energy Research Laboratories
2/75 Bluestone Circuit,
Seventeen Mile Rocks, QLD, AU
Tel: +61 1800 950 865
sales@aerl.com.au

aerl

AERL reserves the right to change any product, product specifications and data without notice to improve reliability, function or design or otherwise.

Copyright © 2024 AERL Pty. Ltd. All Rights Reserved. – REV 005 – 5th March 2024

General Specifications	
Parameter	Typical
Weight	6.2 kg
Dimensions (L x W x H)	432 x 192 x 78 mm
Enclosure Type	Indoor Type 1 / IP20
Mounting Method	2U Rack
Input / Output Power Connectors	Backplane Connector

Characteristics	SRX-R 600/60-48
Nominal Battery Voltage / Vdc Range	48 V / 40 – 60
Max Charge Current	60 A
Nominal Charge Power	3456W @ 48 V
Max PV Input Voltage (VOC)	600 V
Max PV Input Current (IMP)	14 A
Max PV Short Circuit Current (ISC)	20 A
Startup Voltage	30 V
MPP Voltage Range	170 – 500 V
Overload Behavior	Power Limitation
PV Reverse Polarity Protection	Yes
Earth Leakage Current Detection	Yes
Overvoltage Category	DC II
Overvoltage Protection	DC Type II
Safety Protection Class	I
Pollution Degree (Int & Ext)	I
Max Conversion Efficiency	96%
Ambient Operating Temperature Range (Full Rating up to 80% Ambient °C)	-20 to +50 °C
Storage Temperature	-30 to +70 °C
Self-Consumption @ Idle	3.5 W
Allowable Relative Humidity	4 – 95% (non-Condensing)
Cooling Method	Active (User Serviceable)
Display	Indication LED Strip
Required Cabinet Air Exchange Rate (Intake @ 40°C)	25 m ³ /hour
Communications	RS485 / CAN Bus / USB
Certifications	IEC62109-1:2010 EN61000.6.3:2012 EN61000.6.4:2012

Australian Energy Research Laboratories
Head Office
2/75 Bluestone Circuit,
Seventeen Mile Rocks, QLD, AU
Tel: +61 1800 950 865
sales@aerl.com.au

